



# EAZY SERIES


## Unbeatable Reliability

**INKPRINT EAZY 90, 130 and 160** are the ideal economical pad printing solution for textile printing and all general production applications. Available in one and two color configurations.



▲ EAZY90 - 1 Color  
Benchtop model

- ▶ Pneumatic operation guarantees excellent printing uniformity and independent pressure regulation on parts and cliché.
- ▶ The support table of the **INKPRINT EAZY Series** is adjustable in all directions (X-Y-Z axes).
- ▶ The machines can work with the following sealed cup and cliché size:  
**EAZY90** 1C / 90mm diam. (cliché size 100 x 225mm)  
2C RR / 70mm diam. (cliché size 80 x 225mm)  
**EAZY130** 1C / 130mm diam. (cliché size 150x 300mm)  
2C RR / 110mm diam. (cliché size 120x 250mm)  
**EAZY160** 160mm diam. (cliché size 180 x 360mm)  
2C RR / 130mm diam. (cliché size 150 x 300mm)
- ▶ All have a sealed inking system, enabling color changes to be made quickly and less fumes are released in the environment.
- ▶ The machines are easy to operate and require no special maintenance.



◀ EAZY130 - 1 Color  
shown with textile rack  
anvil and factory stand.



▶ EAZY90 - 2 Color RR  
shown with pad shuttle "RR"  
The part remains stationary  
and the pads move side-by-side  
for exact print registration on  
multicolor applications.

# EAZY SERIES

## Inkprint



Scan here to subscribe to our YouTube channel!

### Features

- Electro-pneumatic control
- Micrometrical and adjustable fixture support table
- Photopolymer, steel, and laser plate capability
- Sliding right and left side guard protection
- Foot pedal included
- Adjustable steel dovetail pad assembly



**EAZY160** shown with micrometrical and adjustable fixture support.

### Specifications

	No. of colors	EAZY 90	EAZY 130	EAZY 160
Cycle Speed	1C	Up to 1,200 pph	Up to 1,200 pph	Up to 1,200 pph
	2C RR	Up to 800 pph	Up to 750 pph	Up to 750 pph
Cliché Dimensions	1C	100 x 225mm	150 x 300 mm	180 x 360 mm
	2C RR	80 x 225mm	120 x 250mm	150 x 300mm
Drive		Electro-pneumatic	Electro-pneumatic	Electro-pneumatic
Closed Sealed Cup Dimension	1C	90mm	130mm	160mm
	2C RR	70mm	110mm	130mm
Maximum Printing Area	1C	Ø75mm	Ø115mm	Ø145mm
	2C RR	Ø55mm	Ø95mm	Ø115mm
Horizontal Pad Stroke		125mm	200mm	300mm
Vertical Pad Stroke		80mm	80mm	100mm
Maximum Printing Pressure		680 N	1060 N	1680 N
Electrical Power Supply		220V / 110 V	220V / 110 V	220V / 110 V
Pneumatic Power Supply		6 bar	6 bar	6 bar
Air Consumption		11 litres / cycle	11 litres / cycle	13 litres / cycle
Weight and Factory Stand		198 lbs / 90 kg	265 lbs / 120 kg	309 lbs / 140 kg
Dimensions		HT: 530mm / 21"	HT: 610mm / 25"	HT: 640mm / 25"
		W: 300mm / 15"	W: 390mm / 15"	W: 390mm / 15"
		L: 595mm / 23"	L: 820mm / 32"	L: 1000mm / 39"

Machine specifications are subject to change without notice.



Tagless textile printing with an EAZY 130



**EAZY160** shown with micrometrical and adjustable fixture support.